
Muc-Off

## Safety data sheet According to 1907/2006 EEC Article 31

Printing date: 02.08.2016

### Version: 6

Revision: 02.08.2016



P211 Do not spray on an open flame or other ignition source.

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

#### Trade name: Muc-Off Bike Protect

	(Contd. of page 1)
P280	Wear protective gloves / eye protection.
P271	Use only outdoors or in a well-ventilated area.
P301+P31	0 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P410+P41	2 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P403	Store in a well-ventilated place.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
<ul> <li>Additional</li> </ul>	al information:
EUH066 I	Repeated exposure may cause skin dryness or cracking.
· 2.3 Other	hazards
· Results of	f PBT and vPvB assessment
· PBT: Not	applicable.

• **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

• **Description:** Active substance with propellant

EC number: 918-481-9 Hydrocarbons, C10-C13, n-alkanes, cyclic, <2% aromates, Benzene 50-	
Reg.nr.: 01-2119457273-39 <0.1%	)-<75%
Asp. Tox. 1, H304	
CAS: 106-97-8         butane (containing < 0.1% butadiene (203-450-8))         2.5           EINECS: 203-448-7         Flam. Gas 1, H220; Press. Gas C, H280         2.5           Reg.nr.: 01-2119474691-32         Flam. Gas 1, H220; Press. Gas C, H280         2.5	5-<10%
CAS: 74-98-6         propane         2.5           EINECS: 200-827-9         Flam. Gas 1, H220; Press. Gas C, H280         2.5           Reg.nr.: 01-2119486944-21         Flam. Gas 1, H220; Press. Gas C, H280         2.5	5-<10%

#### · Ingredients according to detergents guidline 648/2004/EC

aliphatic hydrocarbons

· Additional information:

### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

- $\cdot$  After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

#### · 5.1 Extinguishing media

#### • Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

- Carbon dioxide
- Alcohol resistant foam

 $\cdot$  For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 3)

≥ 30%

<sup>-</sup> GB

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

Trade name: Muc-Off Bike Protect

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- · 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurised containers.

- Further information about storage conditions:
- Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

### · Ingredients with limit values that require monitoring at the workplace:

#### 106-97-8 butane (containing < 0.1% butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 4)

(Contd. of page 2)

<sup>-</sup> GF

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

(Contd. of page 3)

### Trade name: Muc-Off Bike Protect

#### 74-98-6 propane

OEL Short-term value: 3600 mg/m<sup>3</sup>, 2000 ppm Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

### $\cdot$ Additional Occupational Exposure Limit Values for possible hazards during processing:

#### Oil mist

WEL Short-term value: 10 mg/m<sup>3</sup>

Long-term value: 5 mg/m<sup>3</sup>

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

· Personal protective equipment:

#### · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

# Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

## Filter A/P2

· Protection of hands:

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

## Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

#### Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### • Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

(Contd. on page 5)

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

**Trade name: Muc-Off Bike Protect** 

(Contd. of page 4)

9.1 Information on basic physical a General Information	nd chemical properties
Appearance:	
Form:	Aerosol
Colour:	Clear
Odour:	Sweetish
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
<b>Boiling point/Boiling range:</b>	-44 °C
Flash point:	-97 °C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/
	vapour mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C:	1 hPa
Density at 20 °C:	0.74 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	89.1 %
Solids content:	0.8 %
9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

×

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

GB

Version: 6

Revision: 02.08.2016

Trade name: Muc-Off Bike Protect

(Contd. of page 5)

• 11.1 Information on toxicological effects • Acute toxicity Based on available data, the classification criteria are not met.					
LD/LC50	values rel	evant for classification:			
Hydrocar	bons,C10	-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%			
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>5000 mg/kg (rabbit)			
Inhalative	LC50/4h	>4951 mg/l (rat)			
Serious ey Respirator CMR effec Germ cell Carcinoge Reproduct STOT-sin STOT-rep Aspiration	e damage ry or skin cts (carcin mutageni onicity Bas tive toxici gle expose peated exp n hazard	ation Based on available data, the classification criteria are not met. //irritation Based on available data, the classification criteria are not met. sensitisation Based on available data, the classification criteria are not met. nogenity, mutagenicity and toxicity for reproduction) (city Based on available data, the classification criteria are not met. sed on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. me Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. me Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met. (ty Based on available data, the classification criteria are not met.			

## **SECTION 12: Ecological information**

#### · 12.1 Toxicity

· Aquatic toxicity:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

EL0 (48h) 1000 mg/l (Daphnia magna)

EL0(72h) 1000 mg/l (Pseudokirchneriella subcapitata)

LL0(96h) 1000 mg/l (Oncorhynchus mykiss (96h))

• 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- $\cdot$  Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

\*

ade name: Muc-Off Bike Protect		
		(Contd. of page
• Uncleaned packaging: • Recommendation: Disposal must be made	according to official regulations	
Keeninkhuuton. Disposai must be made		
SECTION 14: Transport informa	tion	
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	UN1950	
	011930	
<ul> <li>14.2 UN proper shipping name</li> <li>ADR, ADN</li> </ul>	UN1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
· ADR		
<b>V</b>		
· Class · Label	2 5F Gases. 2.1	
	2.1	
· ADN · ADN/R Class:	2 5F	
· IMDG, IATA		
2		
· Class	2.1	
· Label	2.1	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
• 14.5 Environmental hazards:	Volu	
• Marine pollutant:	No	
• 14.6 Special precautions for user	Warning: Gases.	
· Danger code (Kemler):	-	
· EMS Number:	F-D,S-U SW1 Protected from sources of heat.	
· Stowage Code	SW22 For AEROSOLS with a maximum ca	nacity of 1
	litre: Category A. For AEROSOLS with a maximum ca	
	1 litre: Category B. For WASTE AEROSOL	
	C, Clear of living quarters.	
· Segregation Code	SG69 For AEROSOLS with a maximum cap	
	litre: Segregation as for class 9. Stow "separation of the segregation of the second segregation	
	class 1 except for division 1.4. For AEROSC capacity above 1 litre: Segregation as for the	
	subdivision of class 2. For WASTE AEROS	
	Segregation as for the appropriate subdivision	

(Contd. on page 8)

GB –

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

Trade name: Muc-Off Bike Protect

(Contd. of page 7
1L
Code: E0
Not permitted as Excepted Quantity
2
D
1L
Code: E0
Not permitted as Excepted Quantity
UN 1950 AEROSOLS, 2.1

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 28, 29

· National regulations:

Class Share in %

NK 75-<100

· VOC-CH 89.08 %

- · VOC-EU 656.5 g/l
- · Danish MAL Code 5-3

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.

## Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

GB

Printing date: 02.08.2016

Version: 6

Revision: 02.08.2016

#### Trade name: Muc-Off Bike Protect

Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure – Compressed gas Asp. Tox. 1: Aspiration hazard – Category 1 (Contd. of page 8)

GB -